



ENGINEERED TO PERFORM. BUILT TO LAST.

Reliable lift systems for independent repair shops, car dealerships, bodyshops, home enthusiasts, and heavy-duty truck facilities.

Heavy Duty Top Mounted,
Direct-Pull Lifting
Technology

DP18

HEAVY DUTY TWO POST LIFT
18,000 lbs. Capacity



DP18N002BL

FEATURES:

Symmetrical column design

2-stage front and rear arms

Four height configuration models for most ceiling heights

Adjustable width options

- Cylinder rod concealed inside carriage
- Overhead cable equalization
- Single point lock release
- Spring operated arm restraints
- Includes adapter storage bracket
- Durable powder-coated finish
- ALI certified

INCLUDES LOW-PROFILE THREADED
ADAPTER PADS AND (4 each) ADAPTER
EXTENSIONS AT 5" and 10"



LOW-PROFILE ARM DESIGN

- Arms feature a low, 5 1/2" minimum adapter engagement height
- Two-stage with heavy-duty reinforced gusseting
- Easily extended and retracted (61" to 38")



996 Industrial Drive
Madison, IN 47250

Phone: 800.423.1722
Fax: 812.273.7329



www.forwardlift.com



Lit# Forward DP18 CUTSHEET.2021.06 ©2021 Vehicle Service Group™ All rights reserved.

Unless otherwise indicated, Forward Lift, Vehicle Service Group™, Dover and all other trademarks are property of Dover Corporation and its affiliates. Printed in the U.S.A.

SPECIFICATIONS	DP18N000BL/RD*
Capacity	15,000 lbs. (6803kg) 18,000 lbs. (8164kg)
Maximum Rise with 10" Adapter Extensions	83" (2120mm)
Overall Height	DP18N000 154-3/4" (3930mm) DP18N001 175" (4445mm) DP18N002 199" (5054mm)
Height to Shut-Off	147-1/4" (3735mm)
Overall Floor Width	154-3/8" (3921mm)
Width Inside Columns	119-5/8" (3038mm)
Drive Through Clearance	108-1/4" (2750mm)
Arm Reach (Min/Max)	38" / 61" (965mm/1549mm)
Min. Adapter Height	5-1/2" (139mm)
Max. Adapter Height with 10" Extension	15-1/2" (393mm)
Voltage/Amperage	208V/230V, 17 amps
Motor/Phase	1ph/2HP
Ceiling Height Required	155-3/4" (3956mm)

*Lifts available in blue and red
Specifications subject to change without notice or liability.