

DP18PR0

HEAVY DUTY TWO POST LIFT 18,000 lbs. Capacity



FEATURES:

Symmetrical column design

3-stage front and rear arms to service a wider range of vehicles

Three height configuration models for most ceiling heights

Top mounted direct pull technology

- Cylinder rod concealed inside carriage
- Overhead cable equalization
- · Single point lock release
- Spring operated arm restraints
- · Includes adapter storage

SPECIFICATIONS BL=Blue Lift / RD= Red Lift THREE OVERALL HEIGHT OPTIONS / MODELS

12' 10 3/4" Low Ceiling

14' 7" Standard Height

16' 7" Extended Height

147 1/4" Low Ceiling

167 1/4" Standard Height

191 1/4" Extended Height

208V - 230V, 17 amps

12' 11 3/4" Low Ceiling

14' 8" Standard Height

16' 8" Extended Height

18,000 lbs.

12' 10 3/8"

119 5/8"

108 1/4"

30"/61"

2HP / 1Ph

5 1/2"

83 1/4"

- Durable powder-coated finish
- · ALI certified

DP18PN000BL / RD

DP18PN001BL / RD

DP18PN002BL / RD

Rise with 10" Adapter

Height to Shut-Off

Overall Width

Drive-Thru

Inside Columns

Voltage/Amps

Motor/Phase

Arm Reach (Min/Max)

DP18PN000BL / RD

DP18PN001BL / RD

DP18PN002BL / RD

Minimum Adapter Height

Capacity

Extension

HEAVY DUTY 3-STAGE ARM DESIGN

The DP18 Pro's industry leading 30" minimum arm reach creates the needed clearance to swing arms between tires of shorter wheelbase vehicles.

- · 3-stage arms extend and retract from 61" to 30"
- 5 1/2" minimum adapter height from floor



INCLUDES THREADED TRUCK ADAPTERS AND (4 each) 5" and 10" ADAPTER EXTENSIONS





ALI GOLD CERTIFIED

Forward Lift DP18 PRO meets the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.



996 Industrial Drive Madison, IN 47250

Phone: 800.423.1722 Fax: 812.273.7329



Specifications subject to change without notice or liability Lift colors are available in blue (BL) and red (RD)

MINIMUM REQUIRED CEILING HEIGHT