



# F10

SYMMETRICAL TWO POST LIFT  
10,000 lbs. Capacity



## FEATURES:

Symmetrical column design

Versatile 3-stage front and 2-stage rear arms

- Top mounted Direct-Pull lifting technology
- Cylinder rod concealed inside carriage
- Adjustable width options
- Optional extended height kit adds 2'
- Single point lock release
- Powder coated finish
- Includes adapter storage bracket
- ALI Certified

**INCLUDES LOW-PROFILE DROP-IN ADAPTERS AND (4 each) ADAPTER EXTENSIONS AT 3.5" and 5"**



## T100295 Extended Height Kit

The column extension kit is used to add an additional 2 feet (609.6 mm) to the top of the standard lift. This kit includes an extended length hose, return line, and cables to accommodate the extended height. Existing hardware included with the lift is used to attach the extensions.

This kit can be used on the current 400 series model F10 Forward Two Post Lifts.



## SPECIFICATIONS F10N400MBL\*

SPECIFICATIONS	F10N400MBL*
Capacity	10,000 lbs.
Maximum Rise with 5" Extension	76 1/4"
Overall Height	11' 9"
Optional Extended Height	13' 9" with T100295 kit
Overall Width	10' 9" or optional 11' 5"
Drive-Thru	99" or optional 105"
Overhead Switch Height	137 1/8"
Front Arm Reach (Min/Max)	24 1/2" / 58"
Rear Arm Reach (Min/Max)	36" / 58"
Minimum Adapter Height	3 3/4" without extension
Maximum Adapter Height	8 3/4" with 5" extension
Width Inside Columns	109" Standard 115" Optional
Ceiling Height Required	12'
Voltage/Amps	208-230V, 17 amps
Motor/Phase	1PH / 2HP / 60Hz



FWD F10N400MBL



### ALI GOLD CERTIFIED

Forward Lift F10 meets the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.



996 Industrial Drive  
Madison, IN 47250

Phone: 800.423.1722  
Fax: 812.273.7329



www.forwardlift.com

Lit# Forward F10 CUTSHEET.2023.06 ©2023 Vehicle Service Group® All rights reserved.

Unless otherwise indicated, Forward Lift, Vehicle Service Group®, Dover and all other trademarks are property of Dover Corporation and its affiliates.

\*Lifts available in blue (BL) ONLY

Specifications subject to change without notice or liability.