



I-12 PRO

SYMMETRICAL TWO POST LIFT
12,000 lbs. Capacity

FEATURES:

- Symmetrical column design
- Versatile 3-stage front and rear arms
- Four height configuration models
- Adjustable width options



- Overhead cable equalization
- Single point lock release
- Includes adapter storage bracket
- Durable powder-coated finish
- ALI Certified

INCLUDES LOW-PROFILE DROP-IN ADAPTERS AND (4 each) ADAPTER EXTENSIONS AT 1 3/4", 3 1/2" and 5"



SPECIFICATIONS I12N300BL/RD*

Capacity	12,000 lbs.
Maximum Rise with 5" Extension	77 1/2"
Adjustable Overall Height Options	I12N300 13' 10" Standard I12N301 14' 10" Max. Height I12N302 12' 10" I12N303 11' 11"
Overall Width	11' 8" or optional 12' 2"
Drive-Thru	102 3/4" or optional 108 3/4"
Overhead Switch Height Options	I12N300 160 1/8" Standard I12N301 172 1/8" Extended I12N302 148 1/8" I12N303 137 1/8"
Front Arm Reach (Min/Max)	27 3/4" / 59"
Rear Arm Reach (Min/Max)	27 3/4" / 59"
Minimum Adapter Height	4 3/4"
Width Inside Columns	114 7/8" Standard 120 7/8" Optional
Voltage/Amps	208-230V, 17 amps
Motor/Phase	2HP / 1PH



FWD I12N300BL



ALI GOLD CERTIFIED

Forward Lift I12 meets the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.



996 Industrial Drive
Madison, IN 47250

Phone: 800.423.1722
Fax: 812.273.7329



www.forwardlift.com



Lit# Forward I12 CUTSHEET.2023.05 ©2023 Vehicle Service Group* All rights reserved.

Unless otherwise indicated, Forward Lift, Vehicle Service Group®, Dover and all other trademarks are property of Dover Corporation and its affiliates.

*Lifts available in blue (BL) and red (RD)
Specifications subject to change without notice or liability.