

R146RP SWINGARM PRO

HIGH-PERFORMANCE, EXTRA HEIGHT SPEEDCHANGER

VERSATILE HEAVY DUTY CHANGER FOR HIGH VOLUME SHOP USE

Swingarm design with self-centering rim clamps offer a wide variety of wheel and tire combinations

- Exclusive 110v single speed motor provides needed torque
- Air tank located inside column frees space behind machine
- Includes convenient storage cabinet



STANDARD WITH AIR-DRIVEN PLUS9ISA HELPER ARM*

- For large and special tires
- Includes a lower bead lifting roller and pneumatic top bead pressing tool

SHOWN: Helper arm
demounting lower bead



*NOTE: PLUS9ISA IS NOT INSTALLED PRIOR TO DELIVERY



STANDARD PLASTIC MOUNTING / DEMOUNTING HEAD

- Improved design style
- Durable composite for long life

REMOVABLE PEDAL ASSEMBLY

- Allows for easy access maintenance

TECH-FRIENDLY DOUBLE-ACTING SIDE BEAD BREAKER

- Extra wide tool shaft allows operation on tires up to a 15" maximum width
- POWER IN, PARK, and POWER OUT
- Work on low-profile and large steel or alloy rims



WATCH & LEARN!

Scan code to watch
product video

INCLUDES STORAGE CABINET

ROBUST CENTER FRAME

- Extra large 46" frame allows for a maximum tire diameter of 46"
- Arm design for high performance, high volume use



ROTARY®

BY ROTARY SOLUTIONS

R146RP SWINGARM TIRE CHANGER

FEATURES

- 110v drive motor supplies needed torque
- Gear box is supported by steel plates to avoid flex
- Valve tray
- Column-mounted storage case
- Tire paste lubricant and brush

R146RP services:



Optional equipment may be required

SPECIFICATIONS:

External clamping	10" - 26"
Maximum torque to chuck	885 Ft/Lbs (1200 Nm)
Internal clamping	12" - 28.5"
Max. tire diameter	46" (1168 mm)
Max. tire width	15" (380 mm)
Max. bead breaker opening	15" (380 mm)
Bead breaker cylinder power at 145 psi	6,745 Ft/Lbs (3060 kg)
Power supply	110v / 1Ø / 60 Hz

Site Requirements: 110V / 115-145 psi air supply

ROTARY WHEEL SERVICE EQUIPMENT carries a 3 year warranty.
See website for details.

STANDARD EQUIPMENT



PLASTIC TOOL HEAD
VSG800A60 Tool head with support



VSG800A117KIT Tool protection kit for metal mount / demount head (2 x kit)




VSG800A11
Bead breaker protection
Qty. of 1

VSG800A11K / Qty. of 5



VSG800A6KIT
Clamp Protectors / 24" - 26" (4 pcs)

OPTIONAL ACCESSORIES



VSG800A107
FAST FIT MOTORCYCLE ADAPTERS
+ 5" from outside



SMALL WHEEL ADAPTER VSG800A111KIT
Reduces clamping capacity to 8" for ATVs and lawn equipment tires.
- requires VSG800A107 wheel clamps



PART OF **VSG** a **DOVER** company

ROTARY SOLUTIONS

To learn more about all of our automotive service and repair solutions or to contact your local distributor, visit us at www.RotarySolutions.com today.

Need assistance or have questions? We're here to help:
800.445.5438 / Sales: insidesales@rotarysolutions.com
Technical Support: WS-techsupport@rotarysolutions.com

ROTARY SOLUTIONS™

2700 Lanier Drive | Madison, IN 47250, U.S.A.

Lit# Rotary.R146RP.Cutsheet.08.01.2025

©2025 VEHICLE SERVICE GROUP™

All Rights Reserved. Unless otherwise indicated, ROTARY SOLUTIONS™, VEHICLE SERVICE GROUP™, DOVER® and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.